



## PXD-5360F01IR

Article number: 204276

1/2.5" Network Camera, 360° Fisheye Lens, Day&Night, IR-LED, H.264, 2592x1944, PoE

### Mainfeatures

360° 5 megapixel day&night IP camera

25fps @ 1080p Full HD, 12fps @ 2592 x 1944

6x integral IR LED illumination

D-WDR (wide dynamic range)

Alarm recording (Micro SD card)

802.3af compliant PoE standard

1/2.5" CMOS sensor

True day&night mode with IR cut filter (ICR)

Quad codec: 3x H.264 plus 1x MJPEG stream

3DNR (digital noise reduction)

Built in microphone

ImmerVision enables

### Specifications

Sensor size	1/2.5"
Resolution standard	HD 1080p
Imager	CMOS
System	True Day&Night
Sensitivity	0,2 Lux
Sensitivity	(colour) 0,02 (B&W)
Low speed shutter	yes
Low speed shutter	1/1.5~1/425sec.
Wide Dynamic Range (WDR)	D-WDR
Backlight compensation	BLC
IR cut filter	switchable
Automatic electronic shutter (ESC)	1~1/10.000sec.

# PXD-5360F01R

## Specifications continued

Automatic gain control (AGC)	supplied
White balance	automatic, ATW, manual
Stream types	3x H.264, 1x MJPEG multiple
Image transmission rate max.	25 fps
Multicast compliant	yes
Compression standard	H.264, M-JPEG
Lens type	fisheye
Focal length	1,05 mm
Digital zoom	8x
Aperture range (F)	F2.8
Resolution	2592x1944 (4:3), 2048x1536 (4:3), 1920x1080 (16:9), 1280x1024 (5:4), 1280x720 (16:9), 1024x768 (4:3), 800x600 (4:3), 720x576 (4:3), 640x480 (4:3), 352x288 (4:3)
Resolution max.	2592x1944
Horizontal angle of view	180 °
Motion detector	yes
Analysis functions	activity detection, tampering protection
Alarm processing	SD-card recording, FTP, E-Mail, alarm out
Audio	Built-in microphone, speaker
Audio support	yes
Password protection	yes
e-PTZ support	yes
Internal storage	microSD card, SD-HC 32GB
OSD function control	OSD camera setup
Menu languages	German, English, Spanish, French, Russian, Italian
Privacy zones masking	5 areas selectable
Remote configuration	web browser
Web browser	MS Internet Explorer vers. 7.0 or higher, Safari (Quick time), Google Chrome ( Quick time), Mozilla Firefox (Quick time)
Digital Noise Reduction (DNR)	3D-DNR
Digital Noise Reduction (DNR)	yes
Network protocols	TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, IPv4, IPv6, TCP, ARP, NTP, Telnet
Video outputs	no
External connections	RJ-45, alarm output, alarm input, voltage input
Ethernet interface	10Base-T, 100Base-TX
Alarm inputs	1
Alarm outputs	1
Serial interfaces	no
Series	eneo PXD
Dimensions (HxWxD)	149x47mm
Illumination	infrared
Illumination	6x LEDs 850nm
Colour (housing)	RAL9003

## PXD-5360F01IR

### Specifications continued

Housing	indoor
Housing material	plastic
Weight	370g
Heater	no
Power consumption	12W max.
Management Software Support	<a href="http://www.eneo-security.com/en/products/videomanagement.html">www.eneo-security.com/en/products/videomanagement.html</a>
Mounting	wall mount, ceiling mount
ONVIF	yes, Profile S
Power over Ethernet	IEEE 802.3af
Protection rating	n/a
SDK	upon request
Supply voltage	(+/-10%)
Supply voltage	PoE, 12VDC, 24VAC
Temperature range (operation)	-10°C ~ +50°C
Vandalism resistant	no
Certificates	CE
Parts supplied	manual, screw set, Torx key, plug set

### Special features

ImmerVision enables

# PXD-5360F01R

## Available Accessories

Bild	Art. Nr. / Bezeichnung	Beschreibung
	202562 / PNR-5216	Network Video Recorder, 16xIP, 1920x1080, 480fps, 1TB, H.264, MPEG-4, M-JPEG, DVI, D-Sub
	202563 / PNR-5116	Network Video Recorder, 16xIP, 1920x1080, 320fps, 1TB, H.264, MPEG-4, M-JPEG
	204192 / PNR-5108	Network Video Recorder, 8xIP, 1920x1080, 200fps, 1TB, H.264, MPEG-4, M-JPEG
	204193 / PNR-5104	Network Video Recorder, 4xIP, 1920x1080, 120fps, 1TB, H.264, MPEG-4, M-JPEG
	210144 / eneo Scan Device	Management program for eneo IP Cameras
	211974 / ENX-900P	PoE Extender, RJ45, Indoor, up to 100m, Gigabit Ethernet, Half/Full Duplex
	211976 / ECB-1	Media Converter, Indoor, 1x RJ45, 1x SFP
	211979 / ENI-900P	PoE Injector, Gigabit, Indoor, PoE+, RJ45
	211980 / EVX-900R	Media Converter, Indoor, Transmitter-Receiver, 1x RJ45, 1x RJ-11, 12V, up to 1000m
	211981 / EVX-900B	Media Converter, indoor, Transmitter-Receiver, 1x RJ45, 1x BNC, 12V, up to 1000m
	211982 / EPS-1008	PoE Switch, 8x PoE+, 1x RJ45, 1x SFP, 130W, Metal Housing

<p>www. y.com</p> 	<p>211983 / EPS-1016</p>	<p>PoE Switch, 16x PoE+, 2x RJ45, 2x SFP, 250W, 19" Rack</p>
---	--------------------------	--

## Your Contact Person



eneo is a registered trademark of  
 VIDEOR E. Hartig GmbH  
 Carl-Zeiss-Straße 8  
 63322 Rödermark  
 Deutschland  
 Tel.: +49 6074-888-333  
 E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
 Web: [www.eneo-security.com](http://www.eneo-security.com)