



PNR-5304/1TB

Article number: 210047

Network Video Recorder, 4xIP, 1920x1080, 100fps, 1TB, H.264, HDMI, VGA

Mainfeatures

4 channel Full HD Real Time NVR

Full HD 1920x1080 HDMI/VGA main output

Digital PTZ, multiview display

iRAS Software included

4 alarm IN and 1 alarm OUT

2x Sata HDD intern + 1x eSata

Video compression H.264

Multilingual Graphic User Interface (GUI)

IR remote control and mouse control

Management of PNR series

4x PoE Port

ONVIF compatible

Specifications

Compression standard	H.264
Playback	full screen, quad
Display	1920x1200, 1680x1050, 1600x1200, 4 CH HD synchronous playback, Digital Zoom (x2~12) Live & Playback
Displays	OSD - Menu
Operation mode	Quadplex
Max. recording resolution	2592x1944
Recording speed	100 fps @ 1920x1080, 100 fps @ 1280x720, 100 fps @ 704 x 576, 100 fps @ 352 x 288
Max. recording rate	100 fps
Max. recording rate	@1920x1080
Recording	time lapse, event, panic, Text in- POS, Pre-Alarm
Pre-alarm recording	up to 30min.

PNR-5304/1TB

Specifications continued

Backup	Setup import and export
Export of images or clip	USB-port external HDD, via client software, Clip Player, AVI, JPG, BMP
Alarm notification	e-mail notification, Buzzer, remote software, alarm output
Alarm triggers	disk error, eystem error, video loss, Camera Contact, Camera Motion, contact, Text in- Pos
Audio support	yes
Password protection	64 groups, 256 users
HDD hotswap	no
Menu languages	English, German, French, Italian, Spanish, Dutch, Danish, Russian, Polish, Hungarian, Czech, Croatian, Finnish, Turkish, Swedish
Remote access	remote software, browser
Remote configuration	web browser, remote software, mobile client iPhone, iPad, Android
Covert camera mode	available
Network	1x Gigabit Ethernet
Network connection	WAN 1 x 10/100/1000BASE-T, Video In 4 x 10/100BASE-T (POE)
Network protocols	TCP, DHCP, SNS, FEN, Zeroconf
Network data transfer rate	20 Mbps
Data transfer rate	16 Mbps
IP channels	4
Channels total	4
Monitor outputs	HDMI, VGA
Spot monitor	no
USB ports	1x USB 2.0, 1x USB 3.0
Interfaces external storage	eSATA, 4x HDD 4TB
Interfaces external storage	no
Alarm inputs	4
Alarm output	1x Relays NO/NC contact
Audio output	line output
Serial interfaces	RS-232
Operation system	Linux
Series	eneo PNR
Dimensions (HxWxD)	62x300x232mm
19" Rack mountable	no
Number of HHD slots	2x SATA
Control units (external)	mouse, Network Keyboard
Harddisk capacity (internal)	1 TB
Max. harddisk capacity (internal)	8 TB
Weight	2.3 kg
Integrated writer	no
Power consumption	12W(NVR), MAX 48W(PSE)
Supply voltage	12V , 1.0A (Adaptor: 100-240V~, 50/60Hz, 1.5A, 12V , 5A)48V, 1.0A (for PoE)

PNR-5304/1TB

Specifications continued

Temperature range (operation)	+5°C ~ +40°C
Certificates	CE, FCC
Parts supplied	remote viewer software, PSU, manual, IR remote controller, HDD assembly-kit
Remarks	4x POE Ports max. 74W, Please note, currently these models GXB / C / D-1710; GXB / C / D-1720 and GLS-2302H not supported.
Firmware update	via remote software, USB

PNR-5304/1TB

Available Accessories

Bild	Art. Nr. / Bezeichnung	Beschreibung
	74746 / KBD-NSC-100	Network System Controller with 3-Axis Joystick and Jog Shuttle, 5VDC
	206552 / iRAS	Management Software for DLR, DMR, TVR, PNR-53xx, and PNR-5416 Series
	209076 / RAS MOBILE App	Mobile App, for Android and iOS, compatible to DLR, DMR, PNR-53xx, TVR series
	210283 / PLS-5304	Network Video Server, 4-channel, H.264, PoE, 12V, 100fps@720x576, Audio
	210284 / PLS-5308	Network Video Server, 8-channel, H.264, PoE, 12V, 200fps@720x576, Audio
	211105 / eneo Raid Box	Expansion Unit, 5-Bay, without HDD, eSATA, Desktop
	211412 / NPCII	Protocol converter, RS232, TCP/IP, 9-12V
	211461 / HDD-3000SATA Purple	Hard Disk Drive 3TB, SATA, DLR, HDR-5, PNR-53 series expansion
	211462 / HDD-4000SATA Purple	Hard Disc Drive 4TB, SATA DLR, HDR-5, PNR-53 series expansion
	211567 / PNR-KON4	Configuration 1x PNR-53xx with 1-4 eneo IP Cameras
	212067 / HDD-2000SATA Purple	Hard Disk Drive 2TB, SATA, DLR, DMR, HDR-5, PNR-53 Serie expansion

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com