



## PLS-5304

Article number: 210283

Network Video Server, 4-channel, H.264, PoE, 12V, 100fps@720x576, Audio

### Mainfeatures

4-channel Hybrid Extension for PNR-53xx range

Resolution:D1: 720x576 / 960H :960x576 (Pal)

4x Audio input

Motion Detection

iRAS: support live picture display

Frame rate up to 100fps/Sec.@D1

Codec: H.264

RS-485 Telemetry-Interface

Power Supply: 12VDC, PoE

### Specifications

Compression standard	H.264
Stream types	4x H.264
Image transmission rate max.	100 fps
Resolution	720x576 (4:3), 960x576 (4:3)
Resolution max.	960x576
Motion detector	yes
Analysis functions	activity detection
Audio support	yes
Password protection	yes
e-PTZ support	no
Internal storage	no
Menu languages	English
Web browser	MS Internet Explorer vers. 7.0 or higher
Network protocols	DHCP, TCP, HTTP, HTTPS, UPnP, MDNS, Zeroconf

## PLS-5304

### Specifications continued

Video inputs (amount)	4
External connections	RJ-45
Ethernet interface	10Base-T, 100Base-TX, 1000Base-T
Alarm inputs	no
Alarm output	no
Serial interfaces	RS-485
Serial interfaces protocols	Fastrax IIE, Pelco D, Fastrax
Dimensions (HxWxD)	44x200x155mm
Colour	black
Housing	Metal
Weight	0.84 kg
Power consumption	12W max.
ONVIF	no
Power over Ethernet	IEEE 802.3af
Supply voltage	PoE, 12VDC
Temperature range (operation)	0°C ~ +40°C
Certificates	CE, FCC

### Your Contact Person



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Deutschland  
Tel.: +49 6074-888-333  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)