



NXP-880F26

Article number: 212447

1/2.8" Network Board Camera, 1920x1080, Day&Night, 2,6mm, D-WDR, PoE, 12V

Mainfeatures

1/2.8 "2.0 MP Progressive Scan CMOS sensor

Board Camera 42x42x28mm

True Day & Night (TDN)

Corridor format

ONVIF conformance, PoE IEEE802.af

Privacy zones, password protection

Resolution max. 1920x1080 (Full HD)

Quad streaming (H.264, MJPEG)

Noise Reduction (2D-/3D-DNR)

Slot for Micro SD memory card

Cross Web-Browsing

Framerate increase on motion detection

Specifications

Sensor size	1/2.8"
Resolution standard	HD 1080p
Imager	CMOS
Imager	Sony Exmor
System	True Day&Night
Sensitivity	0,2 Lux
Sensitivity	(colour)
Wide Dynamic Range (WDR)	yes
Wide Dynamic Range (WDR)	D-WDR (Digital Wide Dynamic Range)
IR cut filter	switchable
Automatic electronic shutter (ESC)	1~1/10.000sec.
White balance	automatic

NXP-880F26

Specifications continued

Compression standard	H.264, M-JPEG
Stream types	3x H.264, 1x MJPEG multiple
Image transmission rate max.	25 fps
Multicast compliant	yes
Lens type	fixed focal length
Focal length	2,6 mm
Resolution	1920x1080 (16:9), 1280x720 (16:9), 1280x960 (4:3), 1024x768 (4:3), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 640x360 (16:9), 320x240 (4:3)
Resolution max.	1920x1080
Motion detector	yes
Analysis functions	motion detection, Line detection, Field Detector
Alarm processing	SD-card recording, FTP, E-Mail, HTTP/XML
Audio support	yes
Password protection	yes
Password protection	yes
Internal storage	microSD card
OSD function control	Browser setup menu
Menu languages	German, English, Russian, French, Korean
Privacy zones masking	8 zones masking
Remote configuration	web browser
Web browser	MS Internet Explorer vers. 7.0 or higher, Google Chrome (Java), Mozilla Firefox (Java), Safari (Java)
Digital Noise Reduction (DNR)	2D-DNR, 3D-DNR
Digital Noise Reduction (DNR)	yes
Network protocols	TCP/IP, UDP, IPv4, IPv6, RTSP, HTTP, HTTPS, FTP, UPnP, RTP, RTCP, DHCP, ARP, Bonjour, Zeroconf
Ethernet interface	100Base-TX
Alarm inputs	yes
Alarm outputs	yes
Serial interfaces protocols	Pelco D, Fastrax III E
Dimensions (HxWxD)	42x42x28mm
Power consumption	max. 6,7W
ONVIF	yes
Power over Ethernet	yes
Power over Ethernet	IEEE 802.3af
Supply voltage	12VDC
Temperature range (operation)	-20°C ~ +50°C
Certificates	CE

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com