



TPP-72A0030P0A

Article number: 213271

1/2.8" HD-TVI Dome, PTZ, 30x, Day&Night, 4.3-129mm, 1920x1080, WDR, Indoor

Mainfeatures

1/2.8" HD-TVI PTZ dome with Sony CMOS-Sensor

Auflösung max. 1920x1080 (Full HD)

Real time WDR (Wide Dynamic Range) 25/30fps

Auto Calibration

Alarm in- and outputs

30x AF-lens, 4.3~129mm

HD-TVI/AHD and SD-TV signal output

2&3DNR Noise Reduction

Privacy zones, Defog function

Specifications

Sensor size	1/2.8"
Imager	CMOS
Imager	Sony STARVIS
System	True Day&Night
Sensitivity	0,5 Lux
Sensitivity	at F1.6, 50 IRE
Low speed shutter	yes
Manual electronic shutter (MES)	1/5 ~ 1/10.000sec.
Wide Dynamic Range (WDR)	WDR
Flickerless function	yes
Backlight compensation	BLC
IR cut filter	switchable
Automatic electronic shutter (ESC)	1/5 ~ 1/10.000sec.
White balance	automatic, manual, indoor, WAWB, outdoor, fluorescent, Sodium lamp

TPP-72A0030P0A

Specifications continued

Video standard	PAL/NTSC
Signal format	HD-TVI, AHD, SDTV
Synchronization	internal
Lens type	auto focus zoom
Zoom factor	30x
Focal length	4,3 - 129 mm
Digital zoom	8x
MOD (Minimum object distance)	1 m
Aperture range (F)	F1,6~F5,0
Iris control	DC
Resolution	1920x1080 (16:9)
Horizontal angle of view	65,1 - 2,23 °
Motion detector	no
Presets	240 presets
Rotation range	360 °
Speed (manual control)	380 °/Sek.
Preset speed	380 °/Sek.
Menu languages	English
Privacy zones masking	4 areas selectable
Mirror function	flip
Digital Noise Reduction (DNR)	2D-DNR, 3D-DNR
Video outputs	CVBS, HD-TVI
External connections	alarm input/output, voltage input, remote control input
Alarm inputs	4
Alarm outputs	2
Serial interfaces	RS-485
Serial interfaces protocols	Fastrax IIE, Fastrax IIIE, Pelco D, Pelco C (UTC)
Series	eneo Fastrax
Dimensions (HxWxD)	198,9x125mm
Illumination	no
Colour (housing)	black
Housing material	plastic
Weight	1.3kg
Power consumption	12W
Blower	yes
Mounting	ceiling mount
Window heater	no
Supply voltage	12VDC, 24VAC
Temperature range (operation)	0°C ~ +50°C
Text display	title and camera ID
Vandalism resistant	no
Parts supplied	manual, mounting plate

TPP-72A0030P0A

Available Accessories

Bild	Art. Nr. / Bezeichnung	Beschreibung
	74130 / EDC-OPC-2/24V	Pendant Mount Outdoor Dome Housing, Sun Shield, Clear Bubble 6.5", 24VAC
	74135 / EDC-IPC-2/24V	Pendant Mount Indoor Dome Housing with Clear Bubble 6.5", 24VAC
	74136 / EDC-OPS-2/24V	Pendant Mount Outdoor Dome Housing with Sunshield, Tinted Bubble 6.5", 24VAC
	74149 / KBD-2	System Keyboard with 3-Axis Joystick and Jog Shuttle, 12VDC
	74154 / EDC-IDFSW	Flush Mount Dome Housing, White Trimring Smoked Bubble 6.8"
	70449 / NE-128	Voltage supply unit 230V/24V-5A, IP66
	213533 / EDC-OPX/ HD-TVI	Connection wire Fastrax TPP-72A0030P0A Indoor / Outdoor housing

Your Contact Person



eneo is a registered trademark of
 VIDEOR E. Hartig GmbH
 Carl-Zeiss-Straße 8
 63322 Rödermark
 Deutschland
 Tel.: +49 6074-888-333
 E-Mail: info@eneo-security.com
 Web: www.eneo-security.com