

## PS-46



A high brightness 46" LED-backlit display with an OPS slot suitable for professional digital signage applications.

Featuring LED backlighting and 700 nits high brightness for vivid images, the PS-46 public signage display equipped with an OPS slot, built-in scheduler and RS-232/RJ45 remote control function allows easy digital signage installation and management. Flexible landscape or portrait display orientation fulfills different applications. On top of premium-grade LCD panel, the Anti-Burn-in™ technology and HeatControl Sensor prolong product lifespan and ensure reliable operations.

- > LED-backlit technology with FHD 1920 x 1080 resolution
- > 700 nits high brightness
- > Premium-grade panel for high reliability and long product lifetime
- > Anti-Burn-in™ technology
- > AIP technology: 3D Comb Filter/ Deinterlace/ Noise Reduction/PIP and PBP
- > Versatile connectivity: VGA, DVI, HDMI, CVBS, YPbPr, DisplayPort
- > Daisy chain availability: VGA, DVI, RS-232
- > RS-232 and RJ45 allow programmable remote control
- > 15.8 mm bezel width and tiling function for easy video wall setup (support up to 5 x 5)
- > Built-in scheduler allows different programme scheduling
- > HeatControl Sensor automatically activates the internal cooling fan to cool down the temperature
- > OPS slot ready for easy media player integration
- > Built-in speakers
- > Quick switch between internal and external speakers
- > Flexible display orientation: portrait and landscape
- > Rigorous screening of the components for mission-critical 24/7 applications



# PS-46

## Specifications

## PS-46

<b>Panel</b>	Panel Type	LED-Backlit TFT LCD (MVA panel)
	Panel Size	46"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.53 mm
	Brightness	700 cd/m <sup>2</sup> (Typical)
	Contrast Ratio	4000 : 1 (Typical)
	Viewing Angle (H/V)	178°/178° (Typical)
	Display Colour	1.07 B
	Response Time (GTG)	6.5 ms
<b>Frequency (H/V)</b>	H.Freq	31kHz – 91kHz
	V.Freq	50Hz – 85Hz
<b>Input</b>	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	HDMI	HDMI
	Component (YPbPr)	BNC x 3
	CVBS	BNC
	DisplayPort	DisplayPort
<b>Output</b>	DVI/VGA	29-Pin DVI-I
<b>External Control</b>	RS-232 in/out	9-Pin D-Sub
	RJ45	RJ45
<b>Audio</b>	Audio In	1 x Stereo audio in for PC (audio jack, 3.5ø) 1x Stereo audio in (RCA)
	Audio Out	1 x Stereo audio out (RCA)
	Internal Speaker	10W x 2
	External Speaker Out	10W x 2
<b>Other Connectivity</b>	OPS Slot	Yes
<b>Power</b>	Power Supply	Internal
	Power Requirements	100 - 240V, 50 - 60Hz
	Consumption	< 170W (On) < 0.5W (Active Off/Off)
<b>Operating Conditions</b>	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	20%~80% (No condensation)
<b>Storage Conditions</b>	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	5%~95% (No condensation)
<b>Mounting</b>	VESA FPM/PMI	Yes (400 x 400mm/ 400 x 200mm/ 200 x 200mm)
<b>Dimensions</b>	w/o Base (W x H x D)	1053 x 607 x 69 mm (41.5" x 23.9" x 2.7")
	with Base (W x H x D)	1053 x 663 x 400 mm (41.5" x 26.1" x 15.7")
	Packaging (W x H x D)	1309 x 843 x 250 mm (51.5" x 33.2" x 9.8")
<b>Weight</b>	w/o Base	22.0 kg (48.4 lbs)
	with Base	24.0 kg (52.8 lbs)
	Packaging weight	27.5 kg (60.5 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	CB, CE, FCC, RoHS, WEEE, REACH, GOST-R
<b>Accessories</b>	Supplied	CD ROM (user manual), Remote control with AAA batteries, Power cord, 15-Pin D-Sub cable, Power switch cover and screw, Cable tie
	Optional	Stand base



700 nits high brightness panel assures image clarity even under high-ambient light.



Versatile connectivity: VGA, DVI, HDMI, CVBS, YPbPr, DisplayPort, RS-232, RJ45 and audio.



The flexibility in display orientation—either landscape or portrait—means user freedom in fitting whatever setting.



OPS compliant design simplifies digital signage installation and maintenance.

