



MFL-I/LED5-12

Article number: 73923

LED Infrared Illuminator, 850nm, Middle Flood 30°, 5W, 12VDC

Mainfeatures

850nm spectral emission

36 LEDs and built-in CdS sensor

Protection rating: IP66

Low self-heating

30° beam angle

Scene coverage approx 30m/35m (HAD/EXview camera)

Wall mount bracket included

No maintenance required

Specifications

Twilight switch	yes
Mount	1/4" UNC-20
Scene coverage	30 m
Spectral emission	850 nm
Colour	black
Housing	aluminium with plastic cover
Weight	435g
Power consumption	1.5W
Power supply unit	optional
Protection rating	IP66
Supply voltage	12VDC
Radiation angle h	30 °
Temperature range (operation)	-10°C ~ +50°C
Vandalism resistant	no
Certificates	CE

More product information

The best result will be achieved on condition that a camera is used with good sensitivity in the infra-red range, a relative

www.eneo-security.com

lens aperture of F1.4 min. and a mean reflectance factor for spotlight objects.

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com