



## VZT-21A/RJ45

Article number: 75801

Passive Twisted Pair Transmitter or Receiver,  
Composite In/Output, BNC-RJ45

### Main features

Transmission via CAT 5e(6) UTP cable

Up to 400m colour / 600m b&w (at unshielded cable)

Approx. 200m colour / 300m b&w (at shielded cable)

No adjustment necessary

Connectors: BNC plug / RJ-45 jack

### Specifications

Signal transmission	video
Operation mode	passive
Dimensions (HxWxD)	22x25x54mm (w./o. BNC plug)
Model	mini module
Range	400 m
Colour	black
Housing	plastic
Type of unit	transmitter / receiver
Weight	30g
Protection rating	n/a
Supply voltage	-
Temperature range (operation)	-5°C ~ +55°C
Certificates	CE

### More product information

Preferably unshielded twisted-pair cables should be used for the signal transmission. Are there already existing shielded cables which have to be used, the shield must only be earthed on one end, e. g. on transmitter side. We recommend cables in a twisted 2- pair wire bundle configuration (n2x2x0.8mm). The best result will be achieved by using cables with a twist of up to 7-times per meter. Shielded cables, cables with different wire diam., or a connection via patch fields, can considerably reduce the max. possible transmission length.

## Your Contact Person



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Deutschland  
Tel.: +49 6074-888-333  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)