



VK-134

Article number: 91747

1/3" Board Camera, B&W, 3.6mm, 420TVL, Housing, 12VDC

Mainfeatures

CCD b&w board camera with housing

Resolution of 420 horizontal lines

Internal synchronization

Interchangeable lens element

Micro compact version

1/3" CCD Sensor

Automatic shutter control (ESC)

High sensitivity

Supply voltage: 12VDC

Specifications

Sensor size	1/3"
Imager	CCD
Imager	Sony Super HAD Interline Transfer
System	black&white
Sensitivity	0,58 Lux
Sensitivity	at F1.2 (measured), 50 IRE
Low speed shutter	no
Wide Dynamic Range (WDR)	no
Backlight compensation	no
IR cut filter	no
Automatic electronic shutter (ESC)	1/50 ~ 1/100,000sec.
Video standard	CCIR
Synchronization	internal
Lens type	fixed focal length


VK-134

Specifications continued

Focal length	3,6 mm
Digital zoom	no
Aperture Correction (APC)	yes
Horizontal angle of view	69 °
Active picture elements	290,000 (H) 500 x (V) 582
Horizontal resolution	420 TVL
Motion detector	no
e-PTZ support	no
Digital Noise Reduction (DNR)	no
Video outputs	composite (VBS)
External connections	Video (BNC), 12 VDC (DC socket)
Alarm inputs	-
Alarm outputs	-
Serial interfaces	no
Dimensions (HxWxD)	32x32x28mm
Illumination	no
Colour (housing)	black
Housing	indoor
Housing material	metal (aluminium)
Weight	48g
Integrated wall mount	no
Power consumption	1.2W
Window heater	no
Protection rating	n/a
Hidden cable management	no
Supply voltage	12 VDC (+/-10%)
Supply voltage	12VDC
Temperature range (operation)	-10°C ~ +50°C
Vandalism resistant	no
Certificates	CE

VK-134

Available Accessories

Bild	Art. Nr. / Bezeichnung	Beschreibung
	203658 / VT-PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1.0A), Regulated, with DC Plug

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com