



VKC-144/PH

Article number: 91774

1/4" Board Camera, Colour, 3.7mm Pinhole Lens,
380TVL, 12VDC

Main features

1/4" CCD colour board camera

Automatic shutter control (ESC)

Automatic gain control (AGC)

Integrated pinhole lens: F3.5/3.7mm

Low size: 32x32mm

Resolution of 380 horizontal lines

Aperture correction (APC)

Automatic white balance (AWB)

Supply voltage: 12VDC

Specifications

Sensor size	1/4"
Imager	CCD
Imager	1/4" Sony Super HAD Interline Transfer CCD
System	colour
Sensitivity	0,7 Lux
Sensitivity	at F1.2 (measured), 50 IRE
Low speed shutter	no
Wide Dynamic Range (WDR)	no
Backlight compensation	BLC
IR cut filter	standard
Automatic electronic shutter (ESC)	1/50 ~ 1/100,000sec.
Automatic gain control (AGC)	41dB
White balance	automatic (through the lens)
Video standard	PAL

VKC-144/PH

Specifications continued

Synchronization	internal
Lens type	fixed focal length
Focal length	3,7 mm
Digital zoom	no
Aperture Correction (APC)	yes (horizontal)
Horizontal angle of view	51 °
Active picture elements	290,000, 500(H) x 582(V)
Horizontal resolution	380 TVL
Motion detector	no
e-PTZ support	no
Digital Noise Reduction (DNR)	no
Video outputs	composite (CVBS)
Alarm inputs	-
Alarm outputs	-
Serial interfaces	no
Dimensions (HxWxD)	32x32x14mm
Illumination	no
Housing	without housing
Weight	24g
Power consumption	approx. 1.5W
Protection rating	n/a
Hidden cable management	no
Supply voltage	12VDC
Temperature range (operation)	-10°C ~ +40°C
Vandalism resistant	no
Certificates	CE

VKC-144/PH

Available Accessories

Bild	Art. Nr. / Bezeichnung	Beschreibung
	203658 / VT-PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1.0A), Regulated, with DC Plug

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com